


A yellow Liebherr mobile crane is shown in operation, lifting a load of dark material. The crane is mounted on a trailer and is positioned on a paved area. The background features a residential neighborhood with houses and trees under a blue sky with scattered clouds. The crane's jib is extended horizontally, and the load is suspended by cables. The Liebherr logo is visible on the jib.

Der mobile Schnelleinsatzkran 13 HM.1

- Hydraulische Ein-Mann-Montage
- Platzsparende Auslegerluftmontage
- 20°-Ausleger-Steilstellung, stufenlos
- Fahrbar mit 7,5 t LKW
- Stufenlose Antriebe
- Transport mit Vollballast bis zu 80 km/h
- Integrierte Tandemachse mit ABS
- Pneumatische Hebe- und Senkeinrichtung
- Schleifringkörper für unbegrenztes Drehen
- 160°-Ausleger-Ausweichstellung

LIEBHERR



Technische Daten 13 HM.1

Ausladung	20,0 / 22,0 m
Traglast an der Spitze	600 / 500 kg
Maximale Traglast	1500 kg
Hakenhöhe	16,0 m
Hakenhöhe (20° Steilstellung)	20,7 / 21,3 m
Transportabmessungen (L x B x H)	12,9 x 2,4 x 3,5 m
Drehradius	2,3 m

